



Outdoor Rubber Stair Tread

TECHNICAL DATA

PRODUCT DESCRIPTION

Finish & Appearance	#701 RGT Profile Raised Disc, No Factory Finish Square Nose with Relief Cut, Adjustable to 60°
Nominal Dimensions ¹	Available in 48", 60", & 72" Lengths
Available Options	No Special Options Available

PRODUCT PERFORMANCE PROPERTIES

ASTM F2169 – Resilient Stair Treads	Type TS, Class 2, Grade 1
ASTM E648 (NFPA 253) – Critical Radiant Flux	Class I, ≥ 0.45 W/cm ²
ASTM E662 (NFPA 258) – Smoke Density	Passes, ≤ 450
CAN/ULC-S102.2 – Surface Burning	115 Flame Spread Rating 275 Smoke Developed Classification
ASTM D2047 – Static Coefficient of Friction ²	≥ 0.50

PRODUCT INSTALLATION & WARRANTY INFORMATION

Lot Controlled	No
Suitable for In Floor Radiant Heat	Yes
Heat Weldable / Required	No
Indoor / Outdoor Suitability	Suitable for Outdoor Use
Storage Temperature Range ³	60° - 85° F
Installation Temperature Range	40° - 95° F
Required Components for Installation	Excelsior EN-610 Epoxy Nose Filler
Recommended Adhesives ⁴	Excelsior U-705 Urethane Adhesive Excelsior EW-710 Urethane Enhanced Two-Part Epoxy Adhesive
Product Warranty ⁵	Three (3) Year Limited Commercial Warranty

ATTRIBUTES, CERTIFICATIONS, & REGULATORY INFORMATION

- Manufactured in Fostoria, Ohio
- Red List Chemical Free
- Does Not Contain Recycled Materials
- Meets and/or Qualifies for the following:
 - BABAA, Build America, Buy America Act C.F.R.; Title 2 Parts 184 & 200; Pages 57750 – 57790
 - FAR 52.225-9 Buy American-Construction Materials and America Reinvestment and Recovery Act 48 CFR 25.101
 - Build America, Buy America Act Pub. L. No. 117-58, §§ 70901-52 of the Infrastructure Investment and Jobs Act Infrastructure Investment and Jobs Act
 - 49 U.S.C. 5323 (j) (1) and is compliant with the Buy America Act Requirements specifically 49 C.F.R. Part 661
 - 41 U.S.C. Chapter 83; and is compliant with 8302, American materials required for public use



Outdoor Rubber Stair Tread

TECHNICAL DATA

SUPPORT & ADDITIONAL DOCUMENTATION

Product Support Phone & Email	(800) 633 – 3151 / info@flexcofloors.com
Technical Support Phone & Email	(844) 393 – 4044 / solutions@rhctechnical.com
Product Technical Documentation	www.flexcofloors.com
Associated or Related Documentation	Excelsior EN-610 Epoxy Nose Filler Excelsior U-705 Urethane Adhesive Excelsior EW-710 Urethane Enhanced Two-Part Epoxy Adhesive Outdoor Rubber Stair Tread Installation Outdoor Rubber Stair Tread Care & Maintenance Flexco Products Warranty

¹ Nominal Dimensions are the marketed dimensions of the product, tolerances are allowed in the manufacturing process and our tolerance range is what is allowed by the ASTM documentation overseeing the product construction.

² ADA Standards for Accessible Design states the floor surface shall be stable, firm and slip resistant. Our test results utilize the James Machine as described in ASTM D2047 and as described in UL410 for floor covering materials (FCM) utilizing a leather foot under dry conditions. Maintenance processes and commonly utilized site applied finishes, polishes, and other sealers to maintain resilient flooring products will change the walking surface and ultimately the Static Coefficient of Friction. This number indicated dry, out of the box conditions.

³ See installation documents for full installation details regarding approved substrates, job site conditions and acclimation procedures.

⁴ Recommended adhesives listed are recommended to be used to obtain the full listed system warranty that includes a bond performance warranty. Material installed with adhesives other than those listed here or an approved option in writing will only have a product manufacturing and wear warranty, no performance or bond warranty.

⁵ See product warranty for full details regarding limitations and warranty coverage.

The contents contained within this Technical Data Sheet (TDS) may be utilized or copied into another projected related document, but this original document will remain in effect at the time of product installation, this TDS shall not be supplemented or replaced by the resulting project documentation. **Any alterations to the wording or requirements contained in or derived from this document shall void all related warranties.**

See installation information and documents for full installation details regarding substrates, job site conditions, & acclimation procedures. The intent of this document is to provide technical and performance properties of the mentioned adhesive as well as define the intended method of installation for the products in which the adhesive is approved for use. Any installation guidelines are to be considered as a starting point at a minimum for a successful installation. We rely on the expertise and professionals that are installing the products to adjust based on site conditions. Anything that appears to be a link, is and leads to additional information if necessary or provides a means of contact in the event there are any additional questions. Prior to acceptance of this document refer to the product website to confirm that you have the most current revision.

These products are intended for installation by professionals, prior to use the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability.