



Tuflex Spartus Marble Multi-Use Flooring

TECHNICAL DATA

PRODUCT DESCRIPTION

Finish & Appearance	Smooth, No Factory Finish
Nominal Dimensions ¹	25 3/4" (65.4 cm) x 25 3/4" (65.4 cm) x 3/8" (9 mm) Interlocking Tiles @ 4.6046 sq. ft. 27" (68.6 cm) x 27" (68.6 cm) x 3/8" (9 mm) Square Tiles @ 5.0625 sq. ft.

PRODUCT PERFORMANCE PROPERTIES

ASTM E648 (NFPA 253) – Critical Radiant Flux	Class I, $\geq 0.45 \text{ W/cm}^2$
ASTM E662 (NFPA 258) – Smoke Density	Passes, ≤ 450
ASTM D2047 – Static Coefficient of Friction ²	≥ 0.50
ASTM F970 – Static Load Resistance ³	Passes, $< 0.005"$ Indentation @ 250 psi Passes, $< 0.005"$ Indentation @ 1,000 psi Modified
ASTM F925 – Chemical Resistance	Excellent with chemicals listed in standard Additional Chemical List available via chart
ASTM G21 – Resistance to Fungi	Excellent
ASTM D3389 – Abrasion Resistance	Excellent, $\leq 1 \text{ g loss}$ (after 1000 cycles)
ASTM F1514 – Heat Stability	$\Delta E \leq 8$
ASTM F1515 – Light Stability	$\Delta E \leq 8$
ASTM C518 – Thermal Resistance, R	Excellent, $0.178 \text{ F ft}^2\text{h/Btu}$
ASTM D2240 – Durometer Hardness Indentation	$\geq 85 \text{ Shore A}$
ASTM F2772 – Athletic Performance Properties of Indoor Sports Floor Systems	
ASTM F2569 – Shock Absorption	Passes, Class 1
ASTM F2117 – Vertical Ball Rebound	Passes
ASTM F2157 – Vertical Deformation	Passes
ASTM E303 – Surface Friction	Dry; Passes

ACOUSTICAL PERFORMANCE PROPERTIES

6 INCH CONCRETE SLAB	
ASTM E2179 – Sound Reduction	$\Delta IIC 9$
ASTM E492 – Impact Insulation Class	IIC 52
ASTM E90 – Sound Transmission Class	STC 52
6 INCH CONCRETE SLAB / CEILING ASSEMBLY	
ASTM E492 – Impact Insulation Class	IIC 63
ASTM E90 – Sound Transmission Class	STC 67



Tuflex Spartus Marble Multi-Use Flooring

TECHNICAL DATA

PRODUCT INSTALLATION & WARRANTY INFORMATION

Lot Controlled	Yes
Suitable for In Floor Radiant Heat	Yes
Heat Weldable / Required	Not Recommended
Indoor / Outdoor Suitability	Indoor Use Only
Service & Storage Temperature Range ⁴	60° - 85° F
Recommended Adhesives ⁵	Excelsior PS-525 Modified Pressure Sensitive Adhesive Excelsior U-705 Urethane Adhesive Excelsior EW-710 Urethane Enhanced Two-Part Epoxy Adhesive
Product Warranty ⁶	3 Year Exposure to Ice Skates 10 Year Limited Commercial Warranty
Product Limitations	Interlocking material in applications that will be maintained with ride on auto scrubbing equipment, exposed to heavy rolling loads such as expandable bleachers, etc. must be fully adhered to prevent movement under the weight and force of the loads. Exposure to Ice Skates and/or Metal Sports Cleats Warranty is that the product will not wear thru the wear layer, it does not include a warranty that it will not show signs of exposure to these items such as visual marks, cuts, punctures, and/or indentation from the Skates or Cleats in these applications. In these applications it is more about protecting the substrate, skate blades, and/or the cleats themselves to hinder their performance.

ATTRIBUTES, CERTIFICATIONS, & REGULATORY INFORMATION

- Manufactured in Tuscumbia, Alabama
- Health Product Declaration (HPD) Available
- Contributes to LEED v4/4.1 Requirements
- Achieved NSF/ANSI 332 Level 1 Certification
- Achieved FloorScore Certification
- Achieved Certified 24% Pre-Consumer Recycled Content
- Achieved USDA Biopreferred Certification for 30% Biobased Content
- Meets California Department of Public Health V1.2 (CA Section 01350) requirements
- Meets Collaborative for High Performance Schools (CHPS) requirements
- Red List Chemical Free
- Contains Pre-Consumer Recycled Content
- Recyclable Through the Roppe Impact Program
- Meets and/or Qualifies for the following:
 - BABAA, Build America, Buy America Act C.F.R.; Title 2 Parts 184 & 200; Pages 57750 – 57790
 - FAR 52.225-9 Buy American-Construction Materials and America Reinvestment and Recovery Act 48 CFR 25.101
 - Build America, Buy America Act Pub. L. No. 117-58, §§ 70901-52 of the Infrastructure Investment and Jobs Act Infrastructure Investment and Jobs Act
 - 49 U.S.C. 5323 (j) (1) and is compliant with the Buy America Act Requirements specifically 49 C.F.R. Part 661
 - 41 U.S.C. Chapter 83; and is compliant with 8302, American materials required for public use



Tuflex Spartus Marble Multi-Use Flooring

TECHNICAL DATA

SUPPORT & ADDITIONAL DOCUMENTATION

Product Support Phone & Email	(800) 537 – 9527 / sales@roppe.com
Technical Support Phone & Email	(844) 393 – 4044 / solutions@rhctechnical.com
Product Technical Documentation	www.roppe.com
Associated or Related Documentation	Excelsior PS-525 Modified Pressure Sensitive Adhesive Excelsior U-705 Urethane Adhesive Excelsior EW-710 Urethane Enhanced Two-Part Epoxy Adhesive Referenced Standards within Technical Documents Technical Bulletin Tuflex Spartus Multi-Purpose Flooring Installation Tuflex Spartus Multi-Purpose Flooring Care & Maintenance Roppe Products Warranty

¹ Nominal Dimensions are the marketed dimensions of the product, tolerances are allowed in the manufacturing process and our tolerance range is what is allowed by the ASTM documentation overseeing the product construction.

² ADA Standards for Accessible Design states the floor surface shall be stable, firm and slip resistant. Our test results utilize the James Machine as described in ASTM D2047 and as described in UL410 for floor covering materials (FCM) utilizing a leather foot under dry conditions. Maintenance processes and commonly utilized site applied finishes, polishes, and other sealers to maintain resilient flooring products will change the walking surface and ultimately the Static Coefficient of Friction.

³ ASTM F970 testing at loads above 250 psi is outside the scope of the test method and is considered modified. Modification to the testing process for us is the additional load utilizing the same foot as described in the test method by ASTM. Since testing is conducted on flooring product alone, our stated results do not take into consideration chosen adhesive, any utilized underlayments and/or substrates or subfloors. These results should not be construed as an indicator of installed flooring performance.

⁴ See installation documents for full installation details regarding approved substrates, job site conditions and acclimation procedures.

⁵ Recommended adhesives listed are recommended to be used to obtain the full listed system warranty that includes a bond performance warranty. Material installed with adhesives other than those listed here or an approved option in writing will only have a product manufacturing and wear warranty, no performance or bond warranty.

⁶ See product warranty for full details regarding limitations and warranty coverage.

The contents contained within this Technical Data Sheet (TDS) may be utilized or copied into another projected related document, but this original document will remain in effect at the time of product installation, this TDS shall not be supplemented or replaced by the resulting project documentation. **Any alterations to the wording or requirements contained in or derived from this document shall void all related warranties.**

See installation information and documents for full installation details regarding substrates, job site conditions, & acclimation procedures. The intent of this document is to provide technical and performance properties of the mentioned adhesive as well as define the intended method of installation for the products in which the adhesive is approved for use. Any installation guidelines are to be considered as a starting point at a minimum for a successful installation. We rely on the expertise and professionals that are installing the products to adjust based on site conditions. Anything that appears to be a link, is and leads to additional information if necessary or provides a means of contact in the event there are any additional questions. Prior to acceptance of this document refer to the product website to confirm that you have the most current revision.

These products are intended for installation by professionals, prior to use the user must determine the suitability of our products for the intended use, and the user alone assumes all risks and liability.