



# Prime Sports Rubber Sports Flooring

TECHNICAL DATA

## PRODUCT DESCRIPTION

<b>Finish &amp; Appearance</b>	Urethane Bonded Crumb with Characteristic Texture, No Factory Finish
<b>Nominal Dimensions <sup>1</sup></b>	5/32" (3.9 mm), 1/4" (6.3 mm), 3/8" (9.5 mm) , & 1/2" (12.7) Thicknesses Available 34 1/4" (86.9 cm) x 34 1/4" (86.9 cm) Interlocking Tiles @ 8.2 sq. ft. 36" (91.4 cm) x 36" (91.4 cm) Square Tiles @ 9 sq. ft. 48" (1.2 m) x 49 1/2' (15.1 m) Rolls @ 198 sq. ft. Half Rolls & Custom Length Rolls Available, Contact Representative for Details
<b>Color &amp; Chip Percentages</b>	Available in Solid Black & 7 Color Chip Options 10% Chip Content is Standard Special Order up to 90% Chip Content (One or Multiple Colors)

## PRODUCT PERFORMANCE PROPERTIES

<b>ASTM F3041 – Bonded Crumb Rubber</b>	Type I Rolls & Type II Tiles in Standard & Interlocking Class A - ≥ 80% Recycled Content Class B - ≥ 50% and <80% Recycled Content Class C - ≥ 10% and <50% Recycled Content Class D - < 10% Recycled Content
<b>ASTM E648 (NFPA 253) – Critical Radiant Flux</b>	Unclassified, < 0.22 W/cm <sup>2</sup>
<b>ASTM F2859 – Ignition Characteristics</b>	Passes, (FF1-70, 16 CFR 1630)
<b>ASTM D2047 – Static Coefficient of Friction <sup>2</sup></b>	≥ 0.50
<b>ASTM F970 – Static Load Resistance <sup>3</sup></b>	Passes, < 0.005" Indentation @ 250 psi
<b>ASTM F925 – Chemical Resistance <sup>4</sup></b>	Excellent, Additional Chemical List available via chart
<b>ASTM D3389 – Abrasion Resistance</b>	Excellent, ≤ 1 g loss (after 1000 cycles)
<b>ASTM F2199 – Dimensional Stability</b>	Excellent, ≤ 0.050" per linear foot
<b>ASTM F1514 – Heat Stability</b>	ΔE ≤ 8
<b>ASCE 24-14 Flood Resistant Design</b>	FEMA Class 4 when Installed with U-705 Adhesive

## ACOUSTICAL PERFORMANCE PROPERTIES<sup>5</sup>

<b>Recoil &amp; Prime Sports</b>	
<b>6 INCH CONCRETE SLAB / CEILING ASSEMBLY (Nominal 9mm Product Only)</b>	
<b>ASTM E492 - Impact Insulation Class</b>	IIC 57

## PRODUCT INSTALLATION & WARRANTY INFORMATION

<b>Lot Controlled</b>	No
<b>Suitable for In Floor Radiant Heat</b>	Yes
<b>Heat Weldable / Required</b>	Not Recommended / Not Required
<b>Indoor / Outdoor Suitability</b>	Indoor & Outdoor Use



# Prime Sports Rubber Sports Flooring

TECHNICAL DATA

<b>Service &amp; Storage Temperature Range</b> <sup>6</sup>	60° - 85° F
<b>Required Adhesives</b> <sup>7</sup>	Excelsior PS-525 Modified Pressure Sensitive Sensitive Adhesive Excelsior U-705 Urethane Adhesive Excelsior EW-710 Urethane Enhanced Two-Part Epoxy Adhesive
<b>Product Warranty</b> <sup>8</sup>	5 Year Limited Commercial Warranty
<b>Product Limitations</b>	Due to the recycled nature of this product, color variation may be present from piece to piece and roll to roll. Material in areas where free weights and/or dumbbells over 50 lbs. will be used, should be 8 mm thick or greater and must be fully glued. Material is not recommended for basketball, volleyball, or similar playing surfaces.

## SUPPORT & ADDITIONAL DOCUMENTATION

<b>Product Support Phone &amp; Email</b>	(800) 633 – 3151 / <a href="mailto:info@flexcofloors.com">info@flexcofloors.com</a>
<b>Technical Support Phone &amp; Email</b>	(844) 393 – 4044 / <a href="mailto:solutions@rhctechical.com">solutions@rhctechical.com</a>
<b>Product Technical Documentation</b>	<a href="http://www.flexcofloors.com">www.flexcofloors.com</a>
<b>Sustainability Documentation</b>	<a href="#">Ecomedes Product Page</a>
<b>Associated or Related Documentation</b>	<a href="#">Excelsior PS-525 Modified Pressure Sensitive Adhesive</a> <a href="#">Excelsior U-705 Urethane Adhesive</a> <a href="#">Excelsior EW-710 Urethane Enhanced Two-Part Epoxy Adhesive</a> <a href="#">Prime Sports Flooring Installation</a> <a href="#">Prime Sports Flooring Care &amp; Maintenance</a> <a href="#">Flexco Product Warranty</a>

<sup>1</sup> Nominal Dimensions are the marketed dimensions of the product, tolerances are allowed in the manufacturing process and our tolerance range is what is allowed by the ASTM documentation overseeing the product construction.

<sup>2</sup> ADA Standards for Accessible Design states the floor surface shall be stable, firm and slip resistant. Our test results utilize the James Machine as described in ASTM D2047 and as described in UL410 for floor covering materials (FCM) utilizing a leather foot under dry conditions. Maintenance processes and commonly utilized site applied finishes, polishes, and other sealers to maintain resilient flooring products will change the walking surface and ultimately the Static Coefficient of Friction.

<sup>3</sup> ASTM F970 testing at loads above 250 psi is outside the scope of the test method and is considered modified. Modification to the testing process for us is the additional load utilizing the same foot as described in the test method by ASTM. Since testing is conducted on flooring product alone, our stated results do not take into consideration chosen adhesive, any utilized underlayments and/or substrates or subfloors. These results should not be construed as an indicator of installed flooring performance.

<sup>4</sup> ASTM F925 testing is utilized to ensure flooring materials will stand up to certain household standard chemistries. Additional chemical resistance testing performed using this test method is for informational and guidance purposes only. Proper maintenance will influence chemical resistance, but the best defense against a negative effect is to clean the drop/spill from the flooring surface immediately.

<sup>5</sup> Acoustical testing information is provided for information and guidance when selecting flooring materials. Testing is conducted on flooring products with or without underlayments and over laboratory substrates. These results should not be construed as an indicator of installed flooring performance and results.

<sup>6</sup> See installation documents for full installation details regarding approved substrates, job site conditions and acclimation procedures.

<sup>7</sup> Recommended adhesives listed are recommended to be used to obtain the full listed system warranty that includes a bond performance warranty. Material installed with adhesives other than those listed here or an approved option in writing will only have a product manufacturing and wear warranty, no performance or bond warranty.

<sup>8</sup> See product warranty for full details regarding limitations and warranty coverage.

The contents contained within this Technical Data Sheet (TDS) may be utilized or copied into another projected related document. While this original document will remain in effect at the time of product installation, this TDS shall not be supplemented or replaced by the resulting project documentation. Any alterations to the wording or requirements contained in or derived from this document shall void all related warranties.

See installation information and documents for full installation details regarding substrates, job site conditions, & acclimation procedures. The intent of this document is to provide technical and performance properties of the mentioned adhesive and define the intended method of installation for the products in which the adhesive is approved for use. Any installation guidelines are to be considered as a starting point at a minimum for a successful installation. We rely on the expertise and professionals that are installing the products to adjust based on site conditions. Anything that appears to be a link, is and leads to additional information if necessary or provides a means of contact in the event there are any additional questions. Before accepting this document, refer to the product website to confirm that you have the most current revision.

These products are intended for installation by professionals. Prior to use the user must determine the suitability of our products for the intended use. The user alone assumes all risks and liability.