



PixelArt Digitally Printed Flooring, Minimalist Collection

PRODUCT SUBMITTAL

PRODUCT DESCRIPTION

Finish & Appearance	DiamondShield Pro Satin Finish, Subtle Emboss
Nominal Dimensions	19 11/16" (50 cm) x 19 11/16" (50 cm) x 1/8" (3.2 mm)

PRODUCT PERFORMANCE PROPERTIES

ASTM E648 (NFPA 253) – Critical Radiant Flux	Class I, $\geq 0.45 \text{ W/cm}^2$
ASTM E662 (NFPA 258) – Smoke Density	Passes, ≤ 450
ASTM D2047 – Static Coefficient of Friction	≥ 0.50
ASTM F970 – Static Load Resistance	< 0.005" Indentation @ 250 psi < 0.005" Indentation @ 1000 psi
ASTM F925 – Chemical Resistance	Excellent, Additional Chemical List available via chart
ASTM D3389 – Abrasion Resistance	$\leq 1 \text{ g loss}$ (after 1000 cycles)
ASTM F1514 – Heat Stability	$\Delta E \leq 8$
ASTM D2240 – Durometer Hardness Indentation	$\geq 85 \text{ Shore A}$
ASTM G21 – Resistance to Fungi	Excellent
ASTM E2179 – Sound Reduction	ΔIIC 9, Tested on 6 Inch Concrete Slab
ASTM E492 – Impact Insulation Class	IIC 51, Tested on 6 Inch Concrete Slab with Ceiling Assembly
ASTM E90 – Sound Transmission Class	STC 63, Tested on 6 Inch Concrete Slab with Ceiling Assembly

PRODUCT INSTALLATION & WARRANTY INFORMATION

Recommended Adhesives	Excelsior PS-525 Modified Pressure Sensitive Adhesive Excelsior U-705 Urethane Adhesive Excelsior EW-710 Urethane Enhanced Two-Part Epoxy Adhesive
Product Warranty	20 Year Limited Commercial Warranty

IMAGE & COLOR

Available Colors	3000 Monochrome	3001 Element	3002 Refined
	3003 Unadorned	3004 Nuanced	3005 Serene
	3006 Muted	3007 Austere	3008 Understated
	3009 Subtle	3010 Stark	3011 Whisper
	3012 Streamlined	3013 Crisp	3014 Delicate
	3015 Tranquil	3016 Essential	3017 Restrained
	3018 Neutral	3019 Bare	3020 Pure

To ensure complete satisfaction, request a physical sample for final approval before placing an order or writing a specification. While we strive for accurate color representation in our marketing materials, variations may occur between printed and electronic media and the actual product.



PixelArt Digitally Printed Flooring, Minimalist Collection

PRODUCT SUBMITTAL

SUPPORT & ADDITIONAL DOCUMENTATION

Product Support Phone & Email	(800) 537 – 9527 / sales@roppe.com
Technical Support Phone & Email	(844) 393 – 4044 / solutions@rhctechnical.com
Product Technical Documentation	www.roppe.com
Associated or Related Documentation	Excelsior PS-525 Modified Pressure Sensitive Adhesive Excelsior U-705 Urethane Adhesive Excelsior EW-710 Urethane Enhanced Two-Part Epoxy Adhesive Product Warranty PixelArt Flooring Installation Instructions PixelArt Flooring Care & Maintenance Information

The contents contained within this Submittal Sheet may be utilized or copied into another projected related document. While this original document will remain in effect at the time of product installation, this sheet shall not be supplemented or replaced by the resulting project documentation. Any alterations to the wording or requirements contained in or derived from this document shall void all related warranties. Anything that appears to be a link, is and leads to additional information if necessary or provides a means of contact in the event there are any additional questions. Before accepting this document, refer to the product website to confirm that you have the most current revision. These products are intended for installation by professionals. Prior to use the user must determine the suitability of our products for the intended use. The user alone assumes all risks and liability.